

# DM-115P

## 15" XGA 4:3 PCAP Modular Touch Monitor



### Applications

- HMI Solution
- Industrial Automation
- Digital Transformation
- Indoor Ticketing Kiosk
- Security and Surveillance

### Features

- Patented Display Conversion Device (DCD) Technology
- Designed with Aluminum Die-casting Ultra-Thin Front Frame
- IP65 True Front Panel for Waterproof and Dustproof
- Projected Capacitive Touchscreen
- 1024 x 768 Resolution and 350nits Brightness
- Connectors for Display On/Off and External OSD Control
- -20°C to 60°C Operating Temperature



### Ordering Information

Part No.	Description
DM-115P	15" 4:3 XGA (1024 x 768), 350nits, PCAP Touchscreen


### Packing List

Description
1 x DM-115P
Panel Mount Kits

### Specifications

Model		DM-115P
Display	Panel Size	15"
	Panel Type	LCD Panel
	Aspect Ratio	4:3
	Resolution	1024 x 768 (XGA)
	Viewing Angle	176(H) x 176(V)
	Brightness	350cd/m2
	Contrast Ratio	2500:1
	Color Support	16.2M
Touchscreen	Touchscreen Type	Projected Capacitive (PCAP)
	Surface Hardness	7Mohs
	Transparency	90% (±3%)
System	OSD Control	Touch Monitor On/Off, Auto, Menu, Up and Down, Multi-language OSD
	Speaker	N/A
Environment	Operating Temperature	-20°C to 60°C
	Storage Temperature	-20°C to 70°C
	Humidity	10%~80% (non-condensing)
	Vibration	IEC 60068-2-64: 1Grms, random, 5~500 Hz, 1hr/axis
	Shock	IEC 60068-2-27: 15G, half-sine, 11ms duration
General	Certification	CE / FCC
	Ingress Protection	IP 65 Compliant Front Panel
	Material	Front Panel Construction: Die-cast Flat Surface
	Mounting	Panel Mounting
	Dimensions (W x H x D)	377 x 301 x 28.5mm
	Net Weight	4.05kg

## Dimensions



## Viewing

IP65 True Front Panel for Waterproof and Dustproof

Connectors for Display On/Off and External OSD Control

